

## NO2-4FDW-1

Chassis connector with hard Nickel plating, 4 solder contacts, 1 LC-Duplex feedthrough socket and 1 shell ground contact (for SMPTE cable shield), waterproof acc. to IP 65, front panel mount

The chassis connector acts as a "feed-through" allowing simplified installations by connecting a conventional LC-Duplex on the rear. It is built in the standard D size shell and features an automatic sealing cover for maximum dust and dirt protection and a Push-Pull locking mechanism for safe connection. Colored sealings are included to identify the fiber mode.

Not compatible to SMPTE 344M standard. Suitable for indoor (studio) camera links considering specific conditions acc. to IEC 60664-1 like pollution degree 1, overvoltage category 1 and rated voltage. For detailed information ask for the White Paper "opticalCON @ SMPTE Indoor Applications".

## Features & Benefits

<ul style="list-style-type: none"><li>• Suggested OEM equipment connector due to LC front compatibility</li></ul>	<ul style="list-style-type: none"><li>• Designed as feedthrough with automatic sealing shutter</li></ul>
<ul style="list-style-type: none"><li>• Shutter with silicone gasket protects optical connection from dust and dirt</li></ul>	<ul style="list-style-type: none"><li>• Suitable for indoor (studio) camera links considering specific conditions acc. to IEC 60664-1 like pollution degree 1, overvoltage category 1 and rated voltage</li></ul>
<ul style="list-style-type: none"><li>• Accommodates standard LC connectors on the rear for simple installation</li></ul>	<ul style="list-style-type: none"><li>• Connection on the front side either by rugged opticalCON or standard LC connector</li></ul>
<ul style="list-style-type: none"><li>• The low cost of the chassis connector makes it a viable alternative to traditional connectors in fixed installations</li></ul>	<ul style="list-style-type: none"><li>• Water resistant according to IP65 ingress protection in mated condition</li></ul>
<ul style="list-style-type: none"><li>• In case of limited space the chassis can be mounted without rubber gasket. IP rating for this is IP 52.</li></ul>	<ul style="list-style-type: none"><li>• Color coded rubber sealing to identify fiber mode: Multimode - black Single mode PC - blue Single mode APC - green</li></ul>

### Attention! - Product Update

Improved contacts to allow indoor camera routing applications (pollution degree 1, overvoltage category 1) acc. to IEC 60664 up to 240 V ac.