

Funktionsbeschreibung

Der SPATZ OPTO-RCA ist ein universeller Wandler für optisches und coaxiales digitales Audio. Das Gerät hat 2 umschaltbare Eingänge, die mit einem kleinen seitlichen Schiebeschalter ausgewählt werden können. Das jeweils ausgewählte Eingangssignal wird als analoges Stereo ausgegeben. Der Wandler unterstützt Abtastraten von 32; 44.1; 48 und 96 kHz und 2 Kanal LPCM (Linear Pulse Code Modulation). Die Auflösung des S/PDIF Bitstream kann bis 24Bit betragen. 5.1 Audio Signale werden vom Gerät in 2-Kanal gemischt.

Technische Daten

Versorgung	DC 7,5V
Optischer Eingang	1 x TOSLINK
Coaxialer Eingang	1 x Cinch Buchse
Analoger Ausgang	2 x Cinch Buchse
Unterstützte Audioformate	Dolby Digital, DTS bis zu 5.1 Stereo Audio
Grösse	42 x 40 x 22 mm

Functional description

The SPATZ OPTO-RCA is a versatile converter and splitter for digital audio signals. It has 2 switchable inputs, one optical and one coax. The selected input signal is converted to analog audio and available at the STEREO output. The converter supports sample rates of 32; 44.1; 48 und 96 kHz including uncompressed LPCM. The Bitstream may use up to 24 Bit. 5.1 input signals are mixed to 2 channels.

Technical Data

Power supply	DC 7,5V
Optical Input	1 x TOSLINK
Coax Input	1 x RCA Connector
Analog Output	2 x RCA Connector
Supported audio formats	Dolby Digital, DTS up to 5.1 Stereo Audio
Dims	42 x 40 x 22 mm